

Revision date March 2017 1<sup>st</sup> (first) Revision 1of9 Page

## SAFETY DATA SHEET

1. IDENTIFICATION

**Product identifier** 

Other means of identification

Fuel Oil

Marine Diesel Fuel (MDF), Marine Diesel Oil (MDO),

Industrial Diesel Oil (IDO), Automotive Diesel Oil (ADO),

Diesel 1

Recommended use of the chemical and restrictions on

: Used for middle and low rotation diesel engine

use

Manufacturer PT Pertamina (Persero)

> Jl. Medan Merdeka Timur 1A Jakarta Pusat ZIP Code 10110

Phone:1500-000

Email: pcc@pertamina.com

1500-000 **Emergency phone number** 

2. HAZARD IDENTIFICATION

Classification Flammable liquid, category 4

> Skin corrosion/irritation, category 2 Aspiration hazards, category 1

Hazardous to the aquatic environment (chronic), category

2

Signal word Warning

**Hazard statement Physical Hazard** 

H227 - Combustible liquid

**Health Hazard** 

H304 – May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H336 – May cause drowsiness or dizziness

**Environmental Hazard** 

H411 – Toxic to aquatic life with long lasting effects

**Precautionary statement** Prevention

P103 – Read label before use

P280 –Wear protective gloves/protective clothing/eye

protection/face protection.

**Response** 

P301 + P310 -IF SWALLOWED: Immediately call a POISON

CENTER or doctor/physician.

P302 + P352 -IF ON SKIN: Wash with plenty of soap and

water.

P304 + P340 -IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P308 + P313 -IF exposed or concerned: Get medical

advice/attention.

P331 -Do NOT induce vomiting.

Storage

P403 + P233 + P235 –Store in a well-ventilated place.



Revision date : March 2017 Revision : 1<sup>st</sup> (first) Page : 20f9

### SAFETY DATA SHEET

### 2. HAZARD IDENTIFICATION

Keep container tightly closed. Keep cool.

Disposal

P501 -Dispose of contents/container in accordance with

national regulations.

Pictogram







Other hazards which do not result in classification

Irritation to the respiratory tract, dizziness, nausea, and unconsciousness. Repeated contact with the skin for a long time can cause skin irritation or more serious skin

defects.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical NameCAS No.Concentration (%)Hydrocarbon68334-30-5100

#### 4. FIRST AID MEASURES

**Necessary description** 

• In case of eye contact : Flush eyes with plenty of water. Remove contact lenses. If

irritation persists, refer to a doctor/physician.

• In case of skin contact : Wash the contaminated skin with water and soap. Dry it

using dry and clean piece of cloth. Remove contaminated

clothes and wash before reuse.

• If inhaled : Keep the victims away from further exposure with this

product. At the occurrence of irritation to respiratory tract, dizziness, nausea and unconsciousness, seek medical help ordoctors. When breathing stops do

resuscitation from mouth to mouth.

If swallowed : It is an aspiration hazard that may enter lungs and cause

any impairment. If victim ingests more than 0.5 liter, give

1-2 glass of water immediately.

Do not give anything through mouth that can induce nausea or vomiting and to unconscious personnel. Refer

to doctor for medical treatment.

Most important : Repeated skin contact in long time may

symptoms/effects
Indication of Immediate
medical attention and

special treatment needed, if

necessary

Repeated skin contact in long time may cause respiratory irritation, headache, nausea, and unconsciousness.

Swallowed material may be absorbed into the lungs and

cause chemical pneumonitis that needs proper

treatment.

## 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media** : Carbon dioxide (CO<sub>2</sub>), *dry chemical powder* and *foam* Unsuitable extinguishing : -



Revision date : March 2017
Revision : 1<sup>st</sup> (first)
Page : 3of9

# SAFETY DATA SHEET

### 5. FIRE-FIGHTING MEASURES

media

**Specific hazards** 

• Other explosion and fire

hazards

Fire and explosion hazardsmay occur in unprotected

storage tank near fire location.

Flash point°C : 60°C

Flammability value : LEL 0.6%, UEL 7%

Hazardous chemical : Carbon m

composition

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Sulphur

oxide

Special protective actions for

fire fighters

a. Carbon dioxide (CO<sub>2</sub>) : Spray to the origin of fire in the same direction with the

wind.

**b.** Dry chemical powder : Spray to the origin of fire in the same direction with the

wind.

**c.** Foam : If the fire is in a container, spray the foam to inner wall of

the container (not to the ignited liquid) in the same direction with the wind. If the fire occurs because spill, spray to the origin of fire in the same direction with wind until all the fire covered. Do not dispose the spill to the

clean water source (drinking water).

Special protective

equipment for fire-fighter

If fire occurs in limited/indoor/closed area, fire fighter

operator must wear Self-Contained Breathing

Apparatus(SCBA).

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures Keep away from fire source. Avoid direct contact with skin, eye, and clothes. Evacuate personnel to the safe place. Beware of vapor which accumulates to form explosive concentration. Vapor can accumulate in low areas. Use personal protective equipment. Ensure adequate ventilation. Material may cause slippery.

Environmental precautions : Prevent oil spill goes into water ditches, disposal

channels, and seepage into soil.

Procedures : Report spill according to the valid system and procedures.

If spill can go into drainage or streams, do immediate

report to the authority.

Methods and materials for containment and cleaning up

Eliminate all possible ignition condition. Do oil spill absorption using sorbent, sawdust, vermiculate, and other fire retardant material. Clean and dispose cleaned material in the right waste disposal according to valid

regulations.

# 7. HANDLING AND STORAGE

**Precautions for safe handling**: When absorbed by skin, it will cause serious effect. Avoid



Revision date March 2017 1<sup>st</sup> (first) Revision 4of9 Page

# SAFETY DATA SHEET

## 7. HANDLING AND STORAGE

the vapor or mist from being inhaled. Check the H<sub>2</sub>S content. Keep the tank clean. Portable containers for storage must be placed on the ground and the nozzle must be attached to the container during filling to prevent static electricity.

**Conditions for safe storage** (including any

incompatibility)

Store in a cool place. Flammable atmosphere beformed on top of the storage tank, although it is storedbelow flash point. Keep away from combustible andflammable materials. Ensure that container is well closed before material used. Opened container and rest of the material should be closed and placed in stand position to avoid any leakage/spill. Ensure that container

has been labeled rightly.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters** 

: TWA 200 mg/m³ (as total of hydrocarbon vapor) **Exposure limit** 

Skin

**Biological exposure** 

indicator

Not available

Appropriate engineering

control

If product is used in a relatively closed room, a local Ventilation

ventilation must be provided. Ventilation and the

equipment used must be explosion proof.

**Individual protection** measures

Eye and face

protection

Wear eye protection (chemical type goggles).

**Skin protection** 

Wear protective gloves (leather or PVC).

Respiratory protection

Wear respiratory protection when the pollution concentration in the air is higher than the permissible

TLV.

Apply good personal hygiene. **Hygiene practice** 

> Wash hand during break and after handling. Do not eat, and drink, while using this product.

Do not smoke while using this product.

#### PHYSICALAND CHEMICAL PROPERTIES AND SAFETY CHARACTERISTICS

Characteristic **Test Result** 

Organoleptic (physical appearance, color, etc) : Liquid, clear, and bright

Odor Hydrocarbon **Odor threshold** No data available рΗ No data available



Revision date : March 2017 Revision : 1<sup>st</sup> (first) Page : 5of9

### SAFETY DATA SHEET

## 9. PHYSICALAND CHEMICAL PROPERTIES AND SAFETY CHARACTERISTICS

Characteristic Test Result

Melting/freezing point : Cannot be applicated

**Boiling point/boiling range** : 150-600°C

Flammability : Flammable liquid

Flash point :  $60^{\circ}$ C

**Evaporation rate** : No data available **Lower/upper flammability limit and explosion limit** : LEL 0.6%; UEL 7.0%

Vapor pressure : No data available

**Vapor density** : 900 kg/m<sup>3</sup>

Relative density : No data available

Solubility

• Water solubility : Not soluble

Other solubility
 Partition coefficient (n-octanol/water)
 No data available

Auto-ignition temperature: No data availableDecomposition temperature: No data available

**Viscosity** :  $2.5 - 11 \text{ mm}^2/\text{sec}(\text{at } 40^{\circ}\text{C})$ 

#### 10. STABILITY AND REACTIVITY

**Reactivity** : Hazardous substances polimerisation does not occur.

Chemical stability : Stable

Posibility of hazardous

reactions

: No hazardous reaction in normal condition.

**Conditions to avoid** : Heat, fire sparks, flame, or condition that induce

electrostatic.

Incompatible materials

**Hazardous decomposition** 

products

Halogen, strong acid, strong base dan strong oxidizer.

: Carbon monoxide (CO).

#### 11. TOXICOLOGICAL INFORMATION

Comprehensive toxicological/health information

Acute toxicity : Vapor or mist may notcauseacute respiratory irritation

Skin corrosion/ : No data available. Suspected that it may cause mild
 irritation irritation according to compound or product which has

similar structure or composition.

• Serious eye : No data available. Suspected thatit may not cause serious damage/irritation damage but cause mild irritation according to compound

damage but cause mild irritation according tocompound or product which has similar structure or composition.

Respiratory or skin : No data available. Suspected thatit may not cause
 sensitization : respiratory/skin sensitization according to compound

respiratory/skin sensitization according tocompound or product which has similar structure or composition.

• Germ cell mutagenicity : No data available. Suspected that it is not

mutagenaccording tocompound or product which has

similar structure or composition.



Revision date March 2017 1<sup>st</sup> (first) Revision 6of9 Page

## SAFETY DATA SHEET

## 11. TOXICOLOGICAL INFORMATION

No data available. Suspected that it is not carcinogen Carcinogenicity

according to compound or product which has similar

structure or composition.

No data available. Suspected that it is not reproductive Reproductive toxicity

toxicantaccording tocompound or product which has

similar structure or composition.

No data available. Suspected that it may cause narcotic **STOT-single exposure** 

effect according tocompound or product which has

similar structure or composition.

**STOT-repeated** No data available. Suspected that it is not toxic to specific

organ after repeated exposure according tocompound or product which has similar structure or composition.

No data available but this product may cause death if Aspiration hazards

swallowed or enters the airway according tocompound or

product which has similar structure or composition.

Information on the likely

routes exposure

exposure

Symptoms related to the physical, chemical, and toxicological characteristics Inhaled, swallowed, skin contact, and eye contact.

Skin irritation signs and symptoms may include a burning sensation, skin rash, or swelling. Eye irritation signs and symptoms may include a burning sensation and a temporary eye irritation. If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, short breath, and/or fever, the onset of respiratory symptoms may be

delayed for several hours after exposure.

**Delayed and immediate** effects, and also chronic effects from bothshort or long term exposure

No data available. Further testing has not been done.

Numerical measure of

toxicity

: No data available. Further testing has not been done.

**Interative effects** 

Where specific chemical data are not available

No data available. Further testing has not been done. No data available. Further testing has not been done.

Mixture

Mixture vs. Ingredient

information

No data available. Further testing has not been done. No data available. Further testing has not been done.

Other in formation Will not affect human in good hygiene condition.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity** : Soil seepage may cause soil water contamination or

aquifer.

Persistence and degradability

No data available. Further testing has not been done.

**Bioaccumulation potential** 

No data available. Detailed toxic effects is related to concentration nominal value. Further testing has not



Revision date : March 2017 Revision : 1<sup>st</sup> (first) Page : 7of9

#### SAFETY DATA SHEET

## 12. ECOLOGICAL INFORMATION

been done.

**Mobility in soil** : Soil seepage may cause aquifer pollution.

**Other adverse effects** : No data available. Further testing has not been done.

## 13. DISPOSAL CONSIDERATION

**Disposal methods** : This product may be burned in closed place to gain

energy, or burned in incinerator. This product can also be

recycled in the recycling place determined by the

government.

\*Law information: this product sludge waste is classified as hazardous waste (except it is not proven after TCLP (Toxicity Characteristic Leaching Procedure) testing), so that the disposal must follow valid provision.

## 14. TRANSPORT INFORMATION

#### **USA DOT**

UN Number : UN 1202 UN proper shipping name : Diesel fuel

Transport hazard class(es) : 3
Packing group (if available) : PG III
Environmental hazard : Special precautions for user : -

(UN Model Regulation)

## RID / ADR

UN Number : UN 1202 UN proper shipping name : Diesel fuel

Transport hazard class(es) : 3
Packing group (if available) : PG III
Environmental hazard : Special precautions for user

## **IMO**

UN Number : UN 1202 UN proper shipping name : Diesel fuel

Transport hazard class(es) : 3.3
Packing group (if available) : PG III

Environmental hazard : Marine contamination – Hazardous for environment Special precautions for user : If product is transported in large quantity using tanker

ship in international water, it will be transported under International Convention for the Prevention of Pollution

from Ships (MARPOL) Annex I.

#### ICAO / IATA

**UN Number** : UN 1202 **UN proper shipping name** : Diesel fuel

Transport hazard class(es) : 3



Revision date : March 2017 Revision :  $1^{st}$  (first) Page : 80f9

# SAFETY DATA SHEET

## 14. TRANSPORT INFORMATION

Packing group (if available) : PG III Environmental hazard : -Special precautions for user : -

## **15. REGULATORY INFORMATION**

Safety, health, and environmental regulation (specific for the product in question)

- Peraturan Menteri Perindustrian Nomor 23/M-IND/PER/4/2013 tentang Perubahan Atas Peraturan Menteri Perindustrian Nomor 87/M-IND/PER/9/2009 Tentang Sistem Harmonisasi Global Klasifikasi dan Label pada Bahan Kimia
- Basis Industri Manufaktur No. 04/BIM/PER/I/2014 tentang Petunjuk Teknis dan Petunjuk Pengawasan Pelaksanaan Sistem Harmonisasi Global Klasifikasi dan Label Pada Bahan Kimia
- Peraturan Pemerintah Republik Indonesia Nomor 74 Tahun 2001 Tentang Pengelolaan Bahan Berbahaya dan Beracun
- Keputusan Menteri Tenaga Kerja No Kep-187/Men/1999 tentang Pengendalian Bahan Kimia Berbahaya
- Peraturan Menteri Kesehatan Republik Indonesia
   Nomor 70 Tahun 2016 tentang Standar dan
   Persyaratan Kesehatan Lingkungan Kerja Industri
- ACGIH. 2016. TLVs and BEIs.
- Terdaftar pada TSCA EINECS/ELINCS dan AICS
- OSHA 29 CFR 1910.1200

## **16. OTHER INFORMATION**

Composing date

Revision date : March 2017

Key/legend or acronym used :

in the SDS

ADR – European Agreement concerning the International

Carriage of Dangerous Goods by Road

ASTM – American Society for Testing and Materials

CEC - The Coordinating European Council

IATA – The International Air Transport Association ICAO – The International Civil Aviation Organization IMO – The International Maritime Organization

NAB – Nilai Ambang Batas PG – Packaging Group

RID - Regulation concerning the International Carriage of

Dangerous Goods by Rail

**UN - United Nations** 

USA DOT – United States Department of Transportation

Key literature references and :

The data above is cited from but not limited to

sources for data usedin the information sources like DOT ERG No.128, OSHA 29 CFR



Revision date : March 2017
Revision : 1<sup>st</sup> (first)
Page : 90f9

## SAFETY DATA SHEET

# **16. OTHER INFORMATION**

**SDS** 1910.1200

## Disclaimer

The information is composed based on current knowledge and intended to describe safety, health, and environment hazard of the product. Therefore, it should not be construed as guarantee any specific property of the product. All risks while using this product is the user's responsibility. It is not allowed to make change of this document, except there is legal consent.